

Boiler includes incoloy heating elements, magnetic contactors, NEMA-1 panel with boiler and feedwater ON/OFF switch, lamps, McDonnell Miller primary water level control, auxiliary low water cut-off w/manual reset, operating pressure control, high limit w/manual reset, all internal ungrounded circuits subdivided and fused between contactors and source terminals, ASME safety valve, blowdown valve, feedwater stop and check valves, and water gauge set with ball checks and glass protector. UL listed. Meets CSD-1 standard.

Boiler (KW)	Boiler (BHP)	Design Pressure (PSI)	Ship Weight (LBS)	3 Phase		3 Phase			1 Phase	
				Model (480v)	Price (USD)	Model (208v)	Model (240v)	Price (USD)	Model (240v)	Price (USD)
9	0.9	100	400	9BF	\$4,440	9AF	9F	\$4,440	9CF	\$4,490
15	1.5	100	400	15BF	\$4,500	15AF	15F	\$4,500	15CF	\$4,770
18	1.8	100	400	18BF	\$4,570	18AF	18F	\$4,640	18CF	\$4,940
24	2.4	100	445	24BF	\$5,310	24AF	24F	\$5,500	24CF	\$5,620
30	3	100	445	30BF	\$5,700	30AF	30F	\$5,770	30CF	\$6,020
36	3.6	100	500	36BF	\$5,870	36AF	36F	\$6,080	36CF	\$6,550
48	4.8	100	650	48BF	\$6,670	48AF	48F	\$7,410	48CF	\$7,950
60	6	100	650	60BF	\$7,340	60AF	60F	\$8,410	60CF	\$8,540
74	7.4	125	740	74BF	\$7,760	74AF	74F	\$9,330	n/a	n/a
93	9.3	125	835	93BF	\$9,640	93AF	93F	\$10,790	n/a	n/a
112	11.2	125	900	112BF	\$10,060	112AF	112F	\$11,770	n/a	n/a
130	13	125	940	130BF	\$10,330	130AF	130F	\$12,050	n/a	n/a
148	14.8	125	940	148BF	\$10,600	148AF	148F	\$12,180	n/a	n/a
168	16.8	125	1625	168BF	\$12,410	168AF	168F	\$14,010	n/a	n/a
222	22.2	125	1625	222BF	\$13,900	222AF	222F	\$16,120	n/a	n/a

Options:

High pressure ASME design (in lieu of standard design pressure)	125 psi, 9 to 60 kw	\$500
	150 psi, 9 to 222 kw	\$570
Additional pressure switch, mounted and wired with one additional step		\$260
Night Operation Pressure Switch		\$260
Auxiliary high pressure limit switch, auto reset		\$290
High water level alarm (HWL-1)		\$430
Time delay relay		\$110
Vacuum breaker installed above water line		\$100
Control circuit transformer with fused primary and secondary. All boilers require 120 volt control circuit supply. When not available, specify control transformer.		\$360
Progressive sequencer or linear step control with modulating pressure control.	3 to 4 steps	\$650
	5 to 6 steps	\$830
Stainless steel nipples (below water line)		\$210
Low Water Level Alarm (LWL-1)		\$210
Door Interlock		\$80

Notes:

- 1) One instruction manual will be provided with the boiler no charge at the time of the boiler order. One additional manual will be provided no charge at the time of the order if requested. Additional manuals or manuals requested after the boiler is shipped will be invoiced at \$25 each.
- 2) Two sets of submittals will be provided with the boiler no charge at the time of the boiler order. One additional digital (email) set of submittals will be provided no charge at the time of the order if requested. Additional submittals or submittals requested after the boiler is shipped will be invoiced at \$15 each.
- 3) Boiler start-up by a factory authorized representative may be requested for a net cost of \$950 per day plus travel and expenses.

ALL PRICES ARE F.O.B. FACTORY AND SUBJECT TO CHANGE WITHOUT NOTICE.

Lattner Boiler Company
P.O. Box 1527
1411 9th St. SW
Cedar Rapids, IA 52406

Telephone: (800) 345-1527
Fax: (319) 366-0770
Email: info@lattner.com
Website: www.lattner.com